

**KP85 WHITE** is a high-performing polishing powder. Its special formulation allows to reach safely high gloss level even on delicate marble without causing any stain, etching, yellowing and imperfection.



**KP85 WHITE**, thanks the new FINE GRAIN, it dissolves faster with the water and it reacts with the calcium carbonate of the material providing an excellent brightness, leaving vitreous finishing and long lasting resistance against dirt, traffic marks and stains.

**KP85 WHITE** will leave safe floor and not slippery surface.

**KP85 WHITE** is recommended for all materials sensitive to YELLOW base aggressive polishing powders and to be used with PLANETARY FLOOR GRINDERS. The product can also be applied on any calcareous surface. The product does not contain any wax.

## BENEFITS:

- Products don't smell and is suitable to use indoor in every environment: perfect for Hotel lobby application.
- Product has zero volatility when used: do not release dust and do not dispersed in the air.
- Product dissolves faster with water compared to traditional polishing powders: the polishing reaction will become faster and safe.
- Products does not contain yellow pigments like traditional yellow polishing powder: best polishing powder to be use on white base colour marble which may are more sensitive to stains and yellowing.
- Longing last High gloss effect. It add surface resistance to dirt.



## APPLICATION

**KP85 WHITE** can be used whit DISCOLUX PAD by 150-175rpm Single disc machines or by Planetary Head floor grinder at lower speed rotation.

KP 85 WHITE can be used after grinding and honing diamond process or for maintenance marble floors

### How to use.

Clean the surface, making sure to remove any dust and dirt before polishing.

Do not apply on wet surface.

- 1** | Apply 3-4 spoons of product onto the surface to be treated.
- 2** | Add clear water to the product to create a creamy/fluid paste that is easy to distribute.  
As soon as the water has been added to the KP85 WHITE, proceed to apply it to the surface using the polishing machines fitted with DISCOLUX PAD.
- 3** | Continue with the polishing taking care to cover the whole surface area evenly with the powder and water paste. Try to pass over each section of floor the same number of times.
- 4** | During the application process avoid the powder become dry: maintain the mix in the same creamy consistency by adding gradually little water if required.
- 5** | Do not allow the product to dry during the application process. Frequently check consistency and add water as needed to return the product to its fluid/creamy state.
- 6** | Continue to buff with the polishing machine until the surface has reached its maximum shine. The shine results are easy to check during application by removing a small area of product using a squeegee mop or similar, and checking the level of shine achieved.
- 7** | Once the required shine has been achieved, vacuum or remove any residues from the surface and rinse with plenty of clean water.
- 8** | For better result we recommend to wash the floor whit white pad and STONE SOAP.  
After your wash the floor whit clear water and STONE SOAP no further waiting time is necessary.

Once floor its dry it can be open to traffic.

Apply KP85 WHITE to surfaces with a temperature of between +6 and +42°C

Protect any adjacent surfaces not being treated.

Test at prior the result of KP 85 WHITE in a small portion of floor before you proceed full operation to check its suitability for use If you polish to recently laid or grouted marble floors, wait for the adhesive or grout to cure completely.

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

## MAINTENANCE

The floor treated with KP85 WHITE can be well maintained with STONE SOAP, the floor will maintain its gloss and stain proof and dirt proof effect.

For stain-proof and waterproofing protection of a surface polished by KP85 WHITE we recommend KY Waterproofing.

## USE

This product can be used on both indoor and outdoor surfaces.

Suitable for use on: marble, limestone; travertine; marble-cement agglomerates; marble-resin agglomerates.

## COVERAGE

For surface polishing: 60/80 m<sup>2</sup> /kg

For surface maintenance: 80/100 m<sup>2</sup> /kg

## STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE 36 months in the original, sealed packaging, stored in a cool, dry place.

## PACKAGING

5 kg Can - 25 kg Can - 1000Kg Big Bag



The instructions given in this sheet are indicative of an average case history and do not replace the assessment of the professional user who will have to decide on the right product and its best application in relation to the concrete situation they are working with. Before each application, carry out a compatibility test of the product for the use required, for the materials and for the environment for which it is intended, in relation to the professional and personal, environmental and general conditions in which it is to be used.

The supplier, however, not present at the time of application, is not liable for damages of any kind, direct or indirect, to persons, property, the environment, activities or work in progress, resulting from the choice and application of the product as these constitute a free and conscious professional choice of the user.